WEST Search History

Hide Items | Restore | Clear | Cancel

DATE: Tuesday, November 02, 2004

Hide?	Set Name	Query	Hit Count
		DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=ADJ	
☐	L18	L17 NOT l15	12
☐	L17	20010126	31
☐	L16	wireless near8 ((non-real adj time) or non-realtime)	67
☐	L15	L14 and subscriber	19
☐	L14	20010126	26
☐	L13	wireless near8 (non-real adj time)	56
☐	L12	wireless near8 (deliver or delivering or transmit or transmitting) near8 subscriber near8 (non-real adj time)	0
		DB=USPT; PLUR=YES; OP=ADJ	
☐	L11	wireless near8 (deliver or delivering or transmit or transmitting) near8 subscriber near8 (non-real adj time)	0
☐	L10	L9 or l8 or l7 or l6 or l5	5
☐	L9	4207598.pn.	1
☐	L8	4847892.pn.	1
☐	L7	5848139.pn.	1
☐	L6	5894558.pn..pn.	1
☐	L5	6032192.pn.	1
☐	L4	6556826.pn.	1
☐	L3	L2 or l1	2
☐	L2	5604788.pn.	1
☐	L1	5742905.pn.	1

END OF SEARCH HISTORY

WEST Search History

| Hide Items | Restore | Clear | Cancel |

DATE: Tuesday, November 02, 2004

Hide?	Set Name	Query	Hit Count
		DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=ADJ	
☐	L31	L30 and l26	0
☐	L30	(deliver or delivery) near8 wireless near8 (determine or determining)	63
☐	L29	20010126	1
☐	L28	L27 and l26	0
☐	L27	(deliver or delivery) near8 wireless near8 (determine or determining) near8 time	8
☐	L26	20010126	187
☐	L25	(receiver or transceiver) near8 wireless near8 storage	420
☐	L24	L21 and ((non-real adj time) or non-realtime)	0
☐	L23	L21 and l16	0
☐	L22	L21 and (low near8 (load or loading))	0
☐	L21	20010126	53
☐	L20	wireless near8 (predetermined near3 time) near8 (deliver or delivering or transmit or transmitting)	109
☐	L19	wireless near8 (predetermined near3 time)	832
☐	L18	L17 NOT l15	12
☐	L17	20010126	31
☐	L16	wireless near8 ((non-real adj time) or non-realtime)	67
☐	L15	L14 and subscriber	19
☐	L14	20010126	26
☐	L13	wireless near8 (non-real adj time)	56
☐	L12	wireless near8 (deliver or delivering or transmit or transmitting) near8 subscriber near8 (non-real adj time)	0
		DB=USPT; PLUR=YES; OP=ADJ	
☐	L11	wireless near8 (deliver or delivering or transmit or transmitting) near8 subscriber near8 (non-real adj time)	0
☐	L10	L9 or l8 or l7 or l6 or l5	5
☐	L9	4207598.pn.	1
☐	L8	4847892.pn.	1
☐	L7	5848139.pn.	1
☐	L6	5894558.pn..pn.	1

☐	L5	6032192.pn.	1
☐	L4	6556826.pn.	1
☐	L3	L2 or l1	2
☐	L2	5604788.pn.	1
☐	L1	5742905.pn.	1

END OF SEARCH HISTORY

First Hit   Previous Doc   Next Doc   Go to Doc#

Search Forms
Print in Result Set
Search Results   ☐ ▨ Generate Collection ▨ | Print |
Help
User Searches
Preferences
DIS: Entry 19 of 19   File: DWPI   Mar 6, 2001
Logout

DERWENT-ACC-NO: 2001-637590
DERWENT-WEEK: 200368
COPYRIGHT 2004 DERWENT INFORMATION LTD

TITLE: Non-real time messaging system in wireless communication system, has translating controller which generates text messages corresponding to received oral messages using stored data patterns

Basic Abstract Text (1):
NOVELTY - A messaging controller receives oral messages from callers and transmits text messages to communication devices associated with subscribers. A data repository stores data patterns representing oral phrases specific to non-real time messaging system. A translating controller processes received oral messages using stored data patterns and generates corresponding text messages.

PF Application Date (1):
19971231

Previous Doc   Next Doc   Go to Doc#

☐ ▓▓▓ Generate Collection ▓▓▓ | Print |

L15: Entry 16 of 19   File: USPT   Jul 18, 2000

DOCUMENT-IDENTIFIER: US 6091947 A
TITLE: Method and apparatus for accepting and conveying a voice mail message to a
mobile unit in a wireless telephone system

Application Filing Date (1):
19980313

Detailed Description Text (11):
Referring to FIG. 3, a base unit 102, being a complementary structure to the mobile
handset 101, is depicted. The network interface 301 preferably couples to a
standard subscriber telephone line, supplying proper circuit loading, protection,
and ring detection. The network connection may be to the public switched telephone
network, a private switched telephone network such as a PBX, another wireless
telephone system, a wired cable system such as is used for television but shared
with voice facility, a wired cable system such as is used to convey electric power
but shared with data communication facility, or a computer communication network,
such as the Internet or a private local area network having such host computers
equipped with voice facility to originate and accept voice calls. Within the
concept of voice-mail other forms may be suitably referred to as voice mail even
though the message contained therein comprises graphical data, visual data, or
aural data. The inability to convey the mail message directly to the wireless
mobile unit in such a system that triggers the non-real time store-and-forward
delivery method.

L15: Entry 18 of 19   File: USPT   Dec 28, 1999

DOCUMENT-IDENTIFIER: US 6009173 A
TITLE: Encryption and decryption method and apparatus

Application Filing Date (1):
19970131

Brief Summary Text (4):
In a broad sense, efficient paging and security for wireless applications such as
paging have opposing constraints. On the one hand, paging uses its non-real time
capabilities to pack information efficiently to reduce the inefficient use of the
wireless bandwidth. Security measures such as encryption on the other hand
typically add to the information being transmitted over the air. The increased
number of users and the increase in the average size of messages (including text,
facsimile, audio and eventually video information) will only put further
constraints on the use of the limited bandwidth provided.

Detailed Description Text (21):
A personal messaging unit (PMU) or subscriber unit capable of receiving or coupling
to a smartcard is within contemplation of the claims of the present invention.
Actual implementation could include a PMU with contacts for inserting a smartcard,
or a PMU with a separate interface unit for smartcards connected by cable to the
PMU, or a PMU with an embedded smartcard that is either fixed or removable. The
certificate server may be implemented as a self-contained unit (even internal to
the PMU) or as a software program running within a messaging switch (paging or
messaging terminal) or as an external switch outside the paging system domain
altogether. It would be assumed that the certificate server would provide for fully
compatible protocol support with the correspondent entity, including use of
appropriate encryption schemes and access to root authorities for authentications.

Search Forms
Search Results

Help   ☐ [Generate Collection]

User Searches

Preferences Entry 5 of 12   File: USPT   May 20, 2003

Logout

DOCUMENT-IDENTIFIER: US 6567397 B1
TITLE: System and method for wireless exchange of data in a non-real-time data
communications system

Application Filing Date (1):
20000215

Brief Summary Text (2):
The present invention pertains to the field of wireless data communications
systems, and more specifically, to a system and method for non-real time
communication between a fixed base station and a plurality of remote transceivers.